



## AIR ACTUATED FOOT PUMPS

- User friendly foot-actuated design for easy control of moving fluid at tremendous rate
- Uses 3/8" NPTF fluid coupler
- Efficiently operates many industrial and construction single-acting ram applications
- Provides up to 10,000 PSI with standard shop air supply of 110-175 PSI
- A compact yet powerful Air Turbo Motor, U.S. Patent No. 5,341,723 is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patent No. 5,946,912, a built-in by-pass device protects hydraulic system from over pumping damage
- Made of durable light weight corrosion-free aluminum
- 22903B is equipped with mounting holes and mounting hardware for repetitive use applications



**22905**

122 in<sup>3</sup> Usable oil



**22903**

91.5 in<sup>3</sup> Usable oil

Model	Usable Oil Capacity	Pressure Rating	Air Pressure Rating	Output Flow Rate		G.W.
				No Load	Load	
<b>22903</b>	91.5 in <sup>3</sup>	10,000 PSI	110-175 PSI	66 in <sup>3</sup> /min.	11 in <sup>3</sup> /min.	20 Lbs.
<b>22903B</b>	91.5 in <sup>3</sup>			66 in <sup>3</sup> /min.	11 in <sup>3</sup> /min.	20 Lbs.
<b>22905</b>	122 in <sup>3</sup>			65 in <sup>3</sup> /min.	12 in <sup>3</sup> /min.	22 Lbs.